

***CraneWorks, Inc.***  
**Equipment Specification**

**\*\* MANITEX MODEL 2892C BOOM TRUCK \*\***

**Complete Installation On 2008 Sterling LT9513 - 66,000 Lb. GVWR Chassis**

**Manitex 2892C:**

**28-Ton (25.4 tm) Capacity Crane - Behind Cab Mount**

92' four section telescopic boom, 26' to 46' two-section side stow jib, 2 speed planetary hoist with grooved drum and negative draft flange, 3 sheave quick reeve boom point, 300' x 9/16" EIPS IWRC wire rope, 5-ton hook and ball with heavy duty swivel and weight for single line operation, 28-ton 2 sheave load block, boom hoist cylinder, radio anti-two block audible warning and shutoff system, 372-degree non-continuous rotation, pedestal, turret, rotation bearing and swing drive, fully proportional controls and system pressure gauge, dual operators platforms, engine start/stop, foot throttle, outrigger and stabilizer controls at each operator console, LMI audio-visual capacity alert with overload shutoff protection system, 21' 6" A-frame link type crane outriggers and rear under frame 13' 11" power out & down stabilizers with independent operation, audible outrigger stabilizer motion alarm, 70 gallon hydraulic reservoir with 25-micron return line filter, suction strainer & ball type shutoff valve, 3 section hydraulic pump, 20' torsion resistant 4-plate design sub-frame under crane and full length of truck frame, 20' heavy duty steel platform body, bubble level, removable boom rest all painted in standard colors.

**2008 Sterling LT9513 Chassis:**

410 HP MBE diesel engine, 20,000 lb. front axle with flotation tires, 46,000 lb. rear tandem axle, dual 60 gallon fuel tanks, air conditioning, heater and defroster, AM/FM radio, air brakes, Allison 4500RDS automatic transmission, hot shift PTO, axle lock, cruise control & air ride driver seat.

**Call for Current Price**

CONDITIONS: Prices and terms on CraneWorks quotations are not subject to verbal changes or other agreements unless approved in writing by the Home Office of the Seller. All quotations and agreements are contingent upon strikes, accidents, fires, availability of materials and all other causes beyond our control. Prices provided by CraneWorks, Inc. shall be based on costs and conditions existing on date of quotation and are subject to change by the Seller before final acceptance. Terms are payment upon delivery. All quotations are contingent upon compliance with all of the export laws and regulations of the United States. If any such law or regulation cannot be complied with, or if this equipment is prohibited from being exported at any time by the United States Government, any quotation and / or subsequent order(s) received or accepted become null and void.

7795 East Little York Road Houston, Texas 77016  
281-219-7779 Phone 713-491-9359 Fax