

CraneWorks, Inc.

Equipment Specification

**** PALFINGER MODEL PK 32080 CRANE ****

Palfinger PK 32080 D:

219,860 ft./lb. rating – 30.4 mt

- 26'7" horizontal hydraulic reach.
- 14,770 lbs @ 14'1 1/2"
- 14,150 lbs @ 14'5"
- 9,660 lbs @ 20'9"
- 7,190 lbs @ 26'7"
- 5,620 lbs @ 33'1 1/2"
- 4,630 lbs @ 39'4 1/2"
- 3,930 lbs @ 45'11"
- 400 degrees non-continuous rotation.
- Outer boom self-locking system.
- Standard ground controls
- Regenerative, high-speed extensions.
- Hydraulic out & down outriggers, 19' 8" spread.
- 27,500 ft. /lbs. slewing torque.
- Holding checks on all load-bearing cylinders.
- Hydraulic overload protection.
- Base crane dead weight of 6,900 lbs.
- 53 gallon oil tank
- All pins and moving parts equipped with grease zerks fittings.
- Central grease zerks for rotation.
- New Rexroth piston pump 16.1 GPM
- 4 Function Hetric Radio Remote Controls
- Service and operators manuals

Call for Current Price

CONDITIONS: Prices and terms on CraneWorks quotations are not subject to verbal changes or other agreements unless approved in writing by the Home Office of the Seller. All quotations and agreements are contingent upon strikes, accidents, fires, availability of materials and all other causes beyond our control. Prices provided by CraneWorks, Inc. shall be based on costs and conditions existing on date of quotation and are subject to change by the Seller before final acceptance. Terms are payment upon delivery. All quotations are contingent upon compliance with all of the export laws and regulations of the United States. If any such law or regulation cannot be complied with, or if this equipment is prohibited from being exported at any time by the United States Government, any quotation and / or subsequent order(s) received or accepted become null and void.

7795 East Little York Road Houston, Texas 77016
281-219-7779 Phone 713-491-9359 Fax