



RT500-1 SERIES

50-55 US Ton Rough Terrain Crane



FEATURES

- 50-55 tons (45-50 mt)
maximum lifting capacity
- 110 ft. (33.5 m)
maximum boom length
- 170 ft. (51.8 m)
maximum tip height
- Four-section full power mechanically synchronized boom with single lever control
- Swingaway jib offsettable
0°, 15° or 30°
- Two-speed main and auxiliary winches
- Quick-reeving boom head and hook block
- Fully independent multi-position out and down outriggers
- Environmental operator's cab optimizes load visibility and productivity
- Electro-proportional joystick control
- RCI 510 Rated Capacity Indicator
- Easy to read load chart books include range diagrams
- 12 month or 2,000 hour crane warranty and 5 year or 10,000 hours warranty on major weldments

**Simple, Available
and Cost Effective™**

Machines shown may have optional equipment.

TEREX RT 500-1 SERIES

Rough Terrain Cranes

RT 550-1 – 50-1 tons (45 mt)

RT 555-1 – 55-1 tons (50 mt)

110 ft. (33.5 m) FOUR-SECTION, FULL-POWER, MECHANICALLY SYNCHRONIZED BOOM WITH SINGLE LEVER CONTROL

- High strength, four plate construction welded inside and out with stamped impressions to reduce weight.
- Single boom hoist cylinder provides boom elevation of -4° to 76° for easier reeving changes and close radius operation.
- Quick-reeving boom head; no need to remove wedge and socket from rope.
- 360° house lock standard.

ENVIRONMENTAL OPERATOR'S CAB

- Rated Capacity Indicator (RCI) system including anti-two block system with automatic function disconnects.
- Deluxe six-way adjustable operator's seat has mechanical suspension and adjustable head and arm rests.
- Sound and weather insulated for comfort.
- Removable front window, hinged tinted glass skylight, and sliding right-hand window.
- Armrest mounted dual axis controls for winch(s), swing, and boom elevation; foot control pedals for swing brake, boom telescope, and throttle.
- Modular transmission shift and wiper controls.
- Propane heater/defroster.
- 12 volt power outlet.
- Cup holder in dashboard.
- Complete instrumentation. Environmentally-sealed rocker switches. Circuit breakers in cab.

RUGGED, EASY-TO-MANEUVER CARRIER

- Box-type chassis construction with reinforcing cross members.
- Chassis is Terex designed and built with 4x4 X 4 drive.



- Full power-shift transmission with integral torque converter; neutral safety start; 6 speeds forward and reverse.
- Hydraulic four-wheel power steering for 2-wheel, 4-wheel or crab steer.
- Split system air over hydraulic disc brakes on all four wheels.
- Fully independent hydraulic outriggers may be utilized fully extended to 22 ft. (6.91 m), in their 1/2 extended position, or fully retracted, with aluminum pads.
- Tail swing only 11' 6" (3.5 m).
- Standard electronic QSB5.9 185HP (139KW) Tier-II compliant Cummins diesel engine.
- 80 gallon (303 L) fuel tank.
- Earthmover style 26.50 x 25, 26 P.R. tires standard.
- Rear axle centering light standard.

POWERFUL, TWO-SPEED MAIN & AUXILIARY WINCHES, STANDARD

- 533 fpm (163 m/min) maximum line speed, 15,639 lbs. (7093 kg) maximum line pull, 11,250 lbs. (5102 kg) permissible line pull.
- Integral automatic brake.
- Electronic drum indicators.
- Winch drum rollers, grooved drum, tapered drum flanges.

HIGH CAPACITY, DEPENDABLE HYDRAULIC SYSTEM

- Three gear pumps driven off the transmission. Combined system capability is 119 gpm (450 lpm).
- Hydraulic reservoir with 112 gal. (424 l) capacity and full flow oil filtration system.

OPTIONS INCLUDE:

- 32 ft. or 33 to 57 ft. (9.68 or 10.15 to 17.30 m) swing-on jib. Both offset 0°, 15° or 30°.
- Hydraulic heater/defroster, air conditioner.
- Diesel heater/defroster.
- Cold weather starting aid.
- 21.00 x 25, 28 P.R. tires.
- Work lights.
- AM/FM cassette radio.
- Revolving amber light.
- 360° spotlight.
- Pintel hook front and rear.
- Independent rear wheel steering.
- Tire inflation kit.

For more information, product demonstration, or details on purchase, lease and rental plans, please contact your local Terex Cranes Distributor.



TEREX

TEREX Cranes

106 12th Street S.E.

Waverly, IA 50677-9488 USA

TEL: +1 (319) 352-3920

FAX: +1 (319) 352-5727

EMAIL: inquire@terexwaverly.com

WEB: terex.com