



PO31461

NEW FASSI F335A.2.25CW ARTICULATING CRANE

Standard Features

- Lifting Capacity: 20,943 lbs inner capacity
- Outreach: up to 47.83'
- Fassi cranes are developed from a design undertaking aimed at creating products that are market leaders, in terms of both performance and safety.
- Fassi designers work with the most advanced computer science, virtually simulating what will actually happen when the crane is being used: strict exertion tests applied to the prototypes confirm the validity of the design expectations
- The attention to quality begins with the choice of materials and is repeated in the structural details, from the steels to the ecological paintwork applied with procedures able to guarantee the highest levels of chemical and physical resistance and consistency over time
- Design in accordance with European Standard EN 12999*. Exertion test class H1B3
- Evolution is the "TOP" range that includes the most advanced solutions in the field of cranes for trucks
- At the heart of the system there are the electronic Evolution systems: the control unit, digital distributor, remote control, ADC combined by means of a CANBUS transmission protocol, and coordinated by the comprehensive management system IMC (Integral Machine Control)
- The systems, together with the excellent synergy between the double linkage system rods and the ProLink function, result in an exceptional crane performance in terms of speed and power, with the highest levels of safety
- Control unit FX800 – Hydraulic distributor D850 – Command unit RCH – Dynamics control ADC
- D850 "Flow sharing" Digital hydraulic distributor and RCH/RCS Evolution remote control
- FX800 electronic control system
- Continuous rotation on a slew ring with motoreducer
- Recycling and XF valves
- MPES system
- Linkages
- ProLink
- Base for fixing with bolts or integrated subframe



www.crane-works.com

INCLUDED OPTIONS

- Dual side X-over ground controls
- 5-function Danfoss modules
- Danfoss PVEH electrical modules
- Scanreco RRC w/ 5 functions
- Type "V20" winch
- Double Fall Pulley
- Non-supply of oil Tank
- Extra wide hydraulically extendable outriggers
- 2 LED Lights on outer boom w/ RRC Controls

