



www.crane-works.com



CraneWorks – Calgary

9605 48th Street SE
Calgary, AB T2C 2R1
(403) 265-7765 Main
(403) 287-7776 Fax

CraneWorks – Colorado

10200 E. 106th Avenue
Brighton, CO 80601
(303) 286-7555 Main
(303) 286-7595 Fax

CraneWorks – Corp.

7795 E. Little York Road
Houston, TX 77016
(281) 219-7779 Main
(713) 491-9359 Fax

PO 32110

NEW MANITEX 30102C BOOM TRUCK

STANDARD FEATURES

- 2-speed Hoist w/ Grooved Drum
- 5 Ton (4.5 mt) Hook and Ball
- 3-Load Sheave Quick Reeve Boom Head
- Radio Anti-Two Block w/ Lockout
- Boom Hoist Cylinder
- System Pressure Gauge
- 372° Non Continuous Rotation
- Removable Boom Rest
- Engine Start/Stop
- Operator's Service/Parts Manuals
- Boom Length and Angle Indicators
- Mechanical Throttle
- Foot Throttle
- Signal Horn
- Bubble Level
- Beverage Cup Holders
- 4 Section Telescopic Boom
- 335' (102.11m) 9/16" (14.3mm) Rotation Resistant Wire Rope
- Subframe for 22' (6.71 m) Bed
- 70 Gallon (265 liter) Reservoir w/Suction Strainer & Ball Valve
- Pedestal, Turret, Rotation Bearing & Swing System
- Dual Operator Control Stations
- Can Bus Load Moment Indicator w/Internal length Cable-
- Audio/visual Capacity Alert w/ Shut off
- Hermetically sealed Printed Circuit Board Electrical System w/LED Circuit Status Indicators
- Audible Outrigger/Stabilizer Motion Alarm
- A-frame Link Type Front Outriggers (22' 4" Spread Width)
- Out and Down Rear Stabilizers (13 '7" Spread)
- 3-Section Hydraulic Pump
- Outrigger Monitoring System for Verification Only

INCLUDED ITEMS

- 2 piece 26' – 46' jib with hard wired ATB
- 21' heavy hauler steel bed
- Standard mount installation
- 30 ton 3-sheave hook block for 2-4 part line
- Front center stabilizer
- Mounting – FBS
- Control valve for operation of single stabilizer

