

7795 Little York Rd Houston, TX 77016 PH: 866-461-9445 FX: 713-491-9359 www.crane-works.com

Houston - Denver - Kansas City - San Diego - Newark - Calgary

NEW MANITEX 3051 TRACTOR MOUNT BOOM TRUCK

Standard Features

- 2-speed Hoist w/ Grooved Drum
- > 5 Ton (4.5 mt) Hook and Ball
- 3-Load Sheave Quick Reeve Boom Head
- Hard-Wired Anti-Two Block w/ Lockout
- ➢ Boom Hoist Cylinder
- System Pressure Gauge
- > 372° Non Continuous Rotation
- Removable Boom Rest
- Engine Start/Stop
- Operator's Service/Parts Manuals
- Boom Length and Angle Indicators
- Electronic Throttle
- Signal Horn
- Bubble Level
- Beverage Cup Holders
- Outrigger Monitoring System

- 4 Section Telescopic Boom
- > 335' (102.11m) 9/16" (14.3mm) Rotation Resistant Wire Rope
- Subframe for 22' (6.71 m) Bed
- > 70 Gallon (265 liter) Reservoir w/Suction Strainer & Ball Valve
- Pedestal, Turret, Rotation Bearing & Swing System
- Dual Operator Control Stations
- Can Bus Load Moment Indicator w/Internal length Cable-
- Audio/visual Capacity Alert w/ Shut off
- Hermetically sealed Printed Circuit Board Electrical System w/LED Circuit Status Indicators
- Audible Outrigger/Stabilizer Motion Alarm
- ➤ A-frame Link Type Front Outriggers (22' 4" Spread Width)
- Out and Down Rear Stabilizers (13 '7" Spread)
- 3-Section Hydraulic Pump -CCW Rotation is Standard

Included Options

- > Tractor mount rear O/D stabilizers in lieu of standard Subframe A-frame outriggers tractor mount Hydraulic reservoir mount for tractor mount
- Boom rest for tractor mount Front center stabilizer
- Control valve for operation of single stabilizer required w/FBS



















