



www.crane-works.com



CraneWorks – Calgary
9605 48th Street SE
Calgary, AB T2C 2R1
(403) 265-7765 Main
(403) 287-7776 Fax

CraneWorks – Colorado
10200 E. 106th Avenue
Brighton, CO 80601
(303) 286-7555 Main
(303) 286-7595 Fax

CraneWorks – Corp.
7795 E. Little York Road
Houston, TX 77016
(281) 219-7779 Main
(713) 491-9359 Fax

Stock #: **PO29432**

NEW MANITEX 40124S 40-TON BOOM CRANE ON 2015 FREIGHTLINER 108SD STANDARD FEATURES

- 2-speed Hoist w/ Grooved Drum & Hoist Drum Rotation Indicator
- 5 Ton (4.5 mt) Hook and Ball
- 4-Load Sheave Quick Reeve Boom Head
- Wired Anti-Two Block w/ Lockout
- Boom Hoist Cylinder
- System Pressure Gauge
- 360° Area of Operation
- Continuous Rotation
- Ride-around Operator Station with Seat
- Removable Boom Rest
- Engine Start/Stop
- Operator's Service/Parts Manuals
- Boom Length and Angle Indicators
- Air Throttle
- Foot Throttle
- No Free Swing (Free swing is avail. option)
- Signal Horn
- Pilot Controls
- Bubble Level
- 5 Section Telescopic Boom
- 380 (115.82M) 5/8" (16mm) rotation Resistant Wire rope
- Audible Outrigger Motion Alarm
- 100 Gallon (379 liter) Reservoir w/Suction Strainer & Ball Valve
- Outrigger Monitoring System for Verification Only
- Turret, Rotation Bearing & Swing System
- Load Moment Indicator-Audio/Visual Capacity Alert w/Shutoff
- 4 Out-And-down Outriggers, 22'(6.71m) spread including Capacities for Intermediate 13'4" (4.05m) and Retracted 7'2" (2.18m) Spreads
- 2 Retractable Ladders for Easy Access to Bed
- 3-Section Vane Pump
- Lower Frame for 10' (3.05m) flatbed
- Oil Cooler
- ROC solid radio remote outrigger controls & control valve for FBS

INCLUDED OPTIONS

Rear mount installation
35-Ton 3 sheave load block
Cab Heater and A/C
Hydraulic Reservoir Chassis Mounted
10' Steel Bed
Front Stabilizer Jack





www.crane-works.com

Mounting front stabilizer

TRUCK

2015 Freightliner 108SD

Engine: CUM ISL 380 HP

Transmission: Eaton Fuller RTO-14908LL

Cummins exhaust brake integral with variable geometry turbo with on/off dash switch

Front Axle: Detroit DA-F-20.0-5 20k drop single

Front Suspension: Taperleaf, 20k

Rear Axle: MT-40-14X 40k R-Series Tandem

4.88 rear axle ratio

Rear Suspension: Tuftrac 40k rear spring

Fuel Tank: 70 gallon aluminum, located LH

Front Tires & Wheels: Michelin XFE 425/65R22.5 20 ply radial, Alcoa Ivl one

82462X22.5X12.25 10-hub Pilot, aluminum

Rear Tires & Wheels: Michelin XDE m/S 11R22.5 14 ply radial, Alcoa Ivl one 88367x22.5x8.25

10-hub Pilot aluminum disc

Heater, defroster and air conditioner

Driver & Rider Seats: Basic high back air suspension with mechanical lumbar and integrated cushion extension

