

CraneWorks – Calgary 9605 48th Street SE Calgary, AB T2C 2R1 (403) 265-7765 Main (403) 287-7776 Fax CraneWorks – Colorado 10200 E. 106th Avenue Brighton, CO 80601 (303) 286-7555 Main (303) 286-7595 Fax CraneWorks – Corp. 7795 E. Little York Road Houston, TX 77016 (281) 219-7779 Main (713) 491-9359 Fax

Stock #: **PO32118**

NEW MANITEX 40124S 40-Ton Boom Crane Standard Features

- 2-speed Hoist w/ Grooved Drum & Hoist Drum Rotation Indicator
- 5 Ton (4.5 mt) Hook and Ball
- 4-Load Sheave Quick Reeve Boom Head
- Wired Anti-Two Block w/ Lockout
- Boom Hoist Cylinder
- System Pressure Gauge
- 360° Area of Operation
- Continuous Rotation
- Ride-around Operator Station with Seat
- Removable Boom Rest
- Engine Start/Stop
- Operator's Service/Parts Manuals
- Boom Length and Angle Indicators
- Air Throttle
- Foot Throttle
- No Free Swing (Free swing is avail. option)
- Signal Horn
- Pilot Controls
- Bubble Level

- 5 Section Telescopic Boom
- 380 (115.82M) 5/8" (16mm) rotation Resistant Wire rope
- Audible Outrigger Motion Alarm
- 100 Gallon (379 liter) Reservoir w/Suction Strainer & Ball Valve
- Outrigger Monitoring System for Verification Only
- Turret, Rotation Bearing & Swing System
- Load Moment Indicator-Audio/Visual Capacity Alert w/Shutoff
- 4 Out-And-down Outriggers, 22'(6.71m) spread including Capacities for Intermediate 13'4" (4.05m) and Retracted 7'2" (2.18m) Spreads
- 2 Retractable Ladders for Easy Access to Bed
- 3-Section Vane Pump
- Lower Frame for 10' (3.05m) flatbed
- Oil Cooler
- ROC solid radio remote outrigger controls & control valve for FBS

INCLUDED OPTIONS

Rear mount installation
Cab A/C
Hydraulic Reservoir Chassis Mounted
10' Steel Bed
Font Stabilizer Jack
Telemetry Engine Monitoring System
Windshield Cover
Mounting – Front stabilizer









