



www.crane-works.com



CraneWorks – Calgary

9605 48th Street SE
Calgary, AB T2C 2R1
(403) 265-7765 Main
(403) 287-7776 Fax

CraneWorks – Colorado

10200 E. 106th Avenue
Brighton, CO 80601
(303) 286-7555 Main
(303) 286-7595 Fax

CraneWorks – Corp.

7795 E. Little York Road
Houston, TX 77016
(281) 219-7779 Main
(713) 491-9359 Fax

MANITEX 40124S BOOM TRUCK

INSTALLED ON NEW KENWORTH T-800 TANDEM

STANDARD FEATURES

- 2-speed Hoist w/ Grooved Drum & Hoist Drum Rotation Indicator
- 5 Ton (4.5 mt) Hook and Ball
- 4-Load Sheave Quick Reeve Boom Head
- Wired Anti-Two Block w/ Lockout
- Boom Hoist Cylinder
- System Pressure Gauge
- 360° Area of Operation
- Continuous Rotation
- Ride-around Operator Station with Seat
- Removable Boom Rest
- Engine Start/Stop
- Operator's Service/Parts Manuals
- Boom Length and Angle Indicators
- Air Throttle
- Foot Throttle
- No Free Swing (Free swing is avail. option)
- 5 Section Telescopic Boom
- 380 (115.82M) 5/8" (16mm) rotation Resistant Wire rope
- Audible Outrigger Motion Alarm
- 100 Gallon (379 liter) Reservoir w/Suction Strainer & Ball Valve
- Outrigger Monitoring System for Verification Only
- Turret, Rotation Bearing & Swing System
- Load Moment Indicator-Audio/Visual Capacity Alert w/Shutoff
- 4 Out-And-down Outriggers, 22'(6.71m) spread including Capacities for Intermediate 13'4" (4.05m) and Retracted 7'2" (2.18m) Spreads
- 2 Retractable Ladders for Easy Access to Bed
- 3-Section Vane Pump
- Lower Frame for 10' (3.05m) flatbed
- Oil Cooler
- Pilot Controls
- Bubble Level
- ROC solid radio remote outrigger controls & control valve for FBS

INCLUDED ITEMS

- 40124S 40 Ton with 124', 5 Section Telescoping Boom – NO FREE SWING
- New Style Tilting Cab with Heat and Air Conditioning
- Front Center Stabilizer
- 10' Steel Bed
- Rear Mount Installation
- Engine Monitoring System
- Hydraulic Reservoir, Chassis Mounted required when there is no bed
- Front Center Stabilizer (Requires Additional Mounting Charge)
- Mounting--Front Center Stabilizer





www.crane-works.com

TRUCK

- New 2015 Kenworth T-800 Single Steer Tandem Rear Chassis
- Cummins ISX, 450HP, 1650 Ft. Lbs. Diesel Engine
- Cummins Interbrake Exhaust Brake w/ 3 way switch
- Immersion block heater 120V 1000W
- Cruise Control
- Fuller RTLO 16913A Transmission, 13 speed
- Dual power steering gears: 20KK Sheppard M100
- Dana Spicer D2000 20K Front Axle
- Dana Spicer D46-170HP 46K Tandem Rear Axle
- Watson Chalin 13.2K Steerable Pusher Axle
- Neway ADZ246 46K Rear Suspension
- 4.30 Rear Axle Ratio
- Wheel Diff Lock, Both Axles
- Front Tires: Bridgestone M844F 425/65R2 Tires on Aluminum Wheels
- Rear Tires: Bridgestone M799 11R22.5 Tires (Qty 8) on Aluminum Wheels
- 90 US Gallon 24.5 Aluminum Fuel Tank
- 6.9 US Gallon DEF Tank
- Heat/Defrost/Air Conditioning
- Air Cushion plus HB Cloth Drivers Seat
- Toolbox plus HB Cloth Drivers Seat
- AM/FM/WB with BLUETOOTH
- Electric LH & RH Door Locks

Full Specifications Provided Upon Request

