



www.crane-works.com



CraneWorks – Calgary
9605 – 48 Street SE
Calgary, AB T2C 2R1
(403) 265-7769 Main
(403) 287-7776 Fax

CraneWorks – Colorado
10200 E. 106th Avenue
Brighton, CO 80601
(303) 286-7555 Main
(303) 286-7595 Fax

CraneWorks – Corp.
7795 E. Little York Road
Houston, TX 77016
(281) 219-7779 Main
(713) 491-9359 Fax

MANITEX 5096S

MOUNTED ON KENWORTH T-800 TRI-DRIVE

STANDARD FEATURES

- 2-speed Hoist w/ Grooved Drum Roller Tensioner
➤ 5 Ton (4.5mt) Hook and Ball
➤ 4-Load Sheave Quick Reeve Boom Head
➤ Hard Wired Anti-Two Block w/ Lockout
➤ Boom Hoist Cylinder
➤ System Pressure Gauge
➤ 360° Area of Operation
➤ Continuous Rotation
➤ Tilting Cab w/Heater & Windshield Cover
➤ Removable Boom Rest
➤ Engine Start/Stop
➤ Combined Free Swing and Non Free Swing functionality
➤ Operator's Service/Parts Manuals
➤ Boom Length and Angle Indicators
➤ Electronic Throttle
➤ No Free Swing
➤ Hydraulic Rotation Drum Indicator
➤ 3-Section, Vane Pump
➤ Bubble Level
➤ Signal Horn
➤ Diamond Plated Aluminum Decking
➤ 4 Section Telescopic Boom
➤ 400' (122m) or 500' (152m), 5/8" (16mm) Dia. Rotation Resistant Wire Rope
➤ Audible Outrigger Motion Alarm
➤ 115 Gal (435 L) or 150 Gal (568 L) Hyd Reservoir w/Suction Strainer & Ball Valve
➤ Turret, Rotation Bearing & Swing System - Mechanical Houselock
➤ New Load Moment Indicator - Full Visual/Audio Capacity Alert w/Shutoff
➤ ROC Solid outriggers; 4 Out-And-down outriggers, 22' (6.71m) over-all spread. Features a Hand Held Radio Operated Controller and includes capacities for Intermediate 13'4" (4.05m) and Retracted 7'2" (2.18m) Spreads.
➤ Outrigger Monitoring System -Verification Only
➤ Front Bumper Stabilizer - for Short lower frame configurations
➤ 2 Retractable Ladders for Easy Access to Deck
➤ Aluminum Step Ladder - Deck mounted, multi-position
➤ Oil Cooler

INCLUDED ITEMS

- 5004.013, w/ 96', 4 Section Boom
➤ Free Swing / No Free Swing w/ Swing Brake
➤ New Style Tilting Operator's Cab with Heat & A/C
➤ 35 Ton, 3 Sheave Hook Block for 1 – 7 Part Line
➤ Standard Mount Installation
➤ Engine Monitoring System (Truck Telemetry)



TEREX





TRUCK

- 2015 Kenworth T800 Single Tridem
- 485hp/1650 torque Cummins ISX Fuller RTLO16918B transmission
- 20K Front steer axle
- 69K Rear Axles on Neway ADZ Air Ride Suspension
- Diff Locks all Three Axles
- 445/65R 22.5 Bridgestone M844 Front Tires
- 445/65R 22.5 Bridgestone L-315 Rear Tires
- Aluminum Wheels Front and Rear
- Single 120 gal. fuel tank
- Diamond interior w/ GPS & Sat. radio

Detailed specifications upon request