



www.crane-works.com



CraneWorks – Calgary
Bay L 8616 44th Street SE
Calgary, AB T2C 2P6
(403) 265-7769 Main
(403) 287-7776 Fax

CraneWorks – Colorado
10200 E. 106th Avenue
Brighton, CO 80601
(303) 286-7555 Main
(303) 286-7595 Fax

CraneWorks – Corp.
7795 E. Little York Road
Houston, TX 77016
(281) 219-7779 Main
(713) 491-9359 Fax

Stock #: PO30304

NEW PALFINGER 26002E ARTICULATING CRANE STANDARD FEATURES

- Maximum lifting moment 24.9 mt (179,950 ft-lbs).
- Paltronic 50 Overload Protection System.
- Outer boom tilts 15° above horizontal (Power Link Plus).
- Rotation angle 400°.
- Outriggers hydraulically extendable to 18' 6" (R2X) with fixed hydraulic stabilizers (STZS).
- LED marker lights and 10° tilting stabilizer plates.
- 4-function Danfoss control valve.
- BMS-2 radio remote control with Paltronic 50 display on handset, prepared for 6-functions.
- Single ground control station.
- No spare control valve sections.
- Bubble level at both outrigger control stations.
- Load holding valves on slewing, inner, outer and extension cylinder.
- Maintenance-free extension system with return oil utilization.
- Oil tank 53 US gal.(200 l) with return filter, loose. 11.4 HP oil cooler and high pressure filter installed.
- 8 metric ton (17,640 lbs) capacity roller bearing load hook.
- Hour counter with service intervals (12 V power required).
- Mounting hardware kit (UZ 018).

INCLUDED OPTIONS

4-bolt coated mounting hardware kit in lieu of standard
 AOS – Active Oscillation Suppression System
 Cylinder Guard
 6-section hydraulic boom extensions
 Halogen working light – knuckle boom
 R3X Outriggers
 Hydraulic tilting stabilizers

TRUCK

CraneWorks Supplied Chassis -OR- Customer Supplied Chassis

