



Stock #: PO30290

NEW PALFINGER 33002F ARTICULATING CRANE STANDARD FEATURES

- Maximum lifting moment 31.1 mt (224,940 ft-lbs).
- Paltronic 50 Overload Protection System.
- Outer boom tilts 15° above horizontal (Power Link Plus).
- Rotation angle 400°.
- Outriggers hydraulically ext. 21' 8" (R3X)
- Fixed hyd. stabilizers (STZS) with LED lighting.
- 4-function Danfoss control valve.
- Radio remote control with Paltronic 50 display on handset, prepared for 6-functions.
- Single ground control station with LED lighting.
- No spare control valve sections.
- Bubble level at both outrigger control stations.
- Provision for lifting capacity limitation dependent on rotation angle (SHB01).
- Load holding valves on slewing, inner, outer and extension boom cylinder.
- Maintenance-free extension system with return oil utilization.
- Oil tank 53 US gal.(200 l) with return filter, loose.
- 11.4 HP oil cooler and high pressure filter installed.
- 11 metric ton (24,250 lbs) capacity roller bearing load hook.
- Hour counter with service intervals (12 V power required).
- Mounting hardware kit (UZ 018).

INCLUDED OPTIONS

Active Oscillation Suppression System (AOS)
7-section hydraulic boom
180 degree hydraulic tilting stabilizers
F1-81-R parker voac piston pump
2" hose bib, 45 degrees

TRUCK

CraneWorks Supplied Chassis -OR- Customer Supplied Chassis

