



www.crane-works.com



CraneWorks – Calgary
9605 48th Street SE
Calgary, AB T2C 2R1
(403) 265-7765 Main
(403) 287-7776 Fax

CraneWorks – Colorado
10200 E. 106th Avenue
Brighton, CO 80601
(303) 286-7555 Main
(303) 286-7595 Fax

CraneWorks – Corp.
7795 E. Little York Road
Houston, TX 77016
(281) 219-7779 Main
(713) 491-9359 Fax

PO: 96230

NEW TEREX CROSSOVER 8000

STANDARD FEATURES

BASIC MACHINE

- 80 ton (72.6 mt) capacity rating @ 10 ft. (3 m) radius.
- Mainframe Outrigger Hub Base and Crane Upper Super Structure consists of all-steel formed construction.
- X pattern Hyd. swing out and telescopic 3 position (retracted, mid and full extended) 4 outrigger beam system. Approximate outrigger spread is 25' 3" (7.7m) wide by 26' (7.9m) long.
- Outrigger control station in the crane cab.
- No front bumper outrigger required for 360° load capacity.
- Deluxe contoured aluminium fenders - Aluminum Diamond plate decking - Access ladders and steps
- Continuous rotation (no swing stop) foot peddle swing brake and 360 degree swing lock
- Hydraulic Oil cooler

BOOM

- 126' (38.4 m) Four section, full power, mechanically synchronized boom with 190' (57.9 m) max tip height (with jib).
- High strength, four plate construction welded inside and out with embossed side plate holes to reduce weight and increase strength.
- Single boom hoist cylinder provides boom elevation of -4° to 76°.
- Quick reeving boom head; no need to remove the wedge from socket. 5 bottom head sheaves in boom tip.

NEW S-PACE TILTING OPERATOR'S CAB

- Hydraulically tilting fully adjustable from 0 to 18 degrees
- Rated Capacity Limiter (RCL) system including anti-two block system with external cab mounted load indicating lamps (green/yellow/red).
- Deluxe six-way adjustable (heated) operator's seat with air ride & air height adjustment riser and ventilation system at seat base.
- JoyStick Controls in armrests are adjustable fore and aft, pivot up 90° with shutoff controls, mounted controls in armrests for hoist(s), swing and boom elevation;
- Foot control pedals for swing brake and throttle.
- Sound and weather insulated for comfort.
- Digital engine information display



TEREX



- Environmentally sealed rocker switches. Circuit breakers in cab.
- 360-degree house lock standard.
- Removable front window and hinged tinted glass skylight. Tinted safety glass and overhead retractable UV sunscreen.
- Front and top glass windshiled wipers/washers.
- 3 Cab Mounted, manually adjustable work lights.

HYDRAULIC SYSTEM:

- High capacity, full flow oil filtration system with a 150 gallon (568 L) capacity reservoir.
- Single PTO DRIVEN Two pump system (1 piston, 1 gear)- Combined system output is 78 gpm (295 lpm) and up to 4500 psi operating pressure

HOIST:

- Single Main Planetary 2spd Hoist -489 fpm (149 m/min) maximum line speed
18,450 lb. (8369 kg) maximum line pull.
- (Optional Choice) of 3/4" wire rope standard lay or rotation resistant
- Integral automatic brake.

- Grooved drum, tapered flanges, and spring loaded cable roller tensioner for improved spooling.
- Electronic drum rotation pulse indicators in control handles

COUNTERWEIGHT:

- Standard upper counterweight with (optional) auxiliary hoist 3,000lbs, without auxiliary hoist 4,500lbs
- Hydraulic counterweight removal system.

MANUALS:

- Hard Copy Operators Manual - (1) CDROM includes Operators/Parts/Schematics/RCL/Wire Rope (manuals)- (1) CDROM includes AEM Safety Video

INCLUDED ITEMS

- Model Crossover 8000 (80 U.S. Ton (72.6 mt)) BASIC MACHINE (as described above) - 126-ft boom
- English Manual
- Hotshift PTO for automatic transmission
- 12,000 lb heavy cwt package - 2-2,000 LB, 2 - 4,000 lb.
- Rotation resistant wire rope
- Auxiliary hoist included – includes single sheave extension
- Rotation resistant wire rope on auxiliary hoist

- Deluxe A/C and flameless hydraulic heater
- 12-ton overhaul ball
- 60-ton 5-sheave hook block
- (2) remote outrigger ground control stations
- Boom float kit
- Immersion heater for hydraulic reservoir (cold weather package)
- Work light package
- 3rd wrap indicator kit – main hoist
- 3rd wrap indicator kit – auxiliary hoist