

# CRANE WORKS



7795 Little York Rd  
Houston, TX 77016  
PH: 866-461-9445  
FX: 713-491-9359  
www.crane-works.com

Houston - Denver - Kansas City - San Diego - Newark - Calgary

## FLEET # 30-016 MANITEX 30102C

INSTALLED ON 2007 STERLING LT 7501 CHASSIS

### STANDARD FEATURES

- 2-speed Hoist w/ Grooved Drum
- 3-Load Sheave Quick Reeve Boom Head
- 335' (102.11m) 9/16" (14.3mm) Rotation Resistant Wire Rope
- Dual Operator Control Stations
- Radio Anti-Two Block w/ Lockout
- Boom Hoist Cylinder
- 3-Section Hydraulic Pump
- System Pressure Gauge
- 372° Non Continuous Rotation
- Removable Boom Rest
- Engine Start/Stop
- Operator's Service/Parts Manuals
- Boom Length and Angle Indicators
- Mechanical Throttle
- Foot Throttle
- Signal Horn
- Bubble Level
- Beverage Cup Holders
- 4 Section Telescopic Boom
- Subframe for 22' (6.71 m) Bed
- 70 Gallon (265 liter) Reservoir w/Suction Strainer & Ball Valve
- Pedestal, Turret, Rotation Bearing & Swing System
- Load Moment Indicator w/Internal length Cable- Audio/visual Capacity Alert w/ Shut off
- Hermetically sealed Printed Circuit Board Electrical System w/LED Circuit Status Indicators
- Audible Outrigger/Stabilizer Motion Alarm
- A-frame Link Type Front Outriggers (22' 4" Spread Width)
- Out and Down Rear Stabilizers (13' 7" Spread)





[www.crane-works.com](http://www.crane-works.com)

## INCLUDED ITEMS

- Basic Machine w/102' Four-Section Telescopic Boom
- 21' flatbed body with diamondette steel floor
- Standard Mount Installation LMI
- 35 Ton, 3 Sheave Hook Block for 2 – 4 Part Line
- 5 Ton overhaul ball
- 2 Piece – 26' to 46' jib
- Front Center Stabilizer (Requires Additional Mounting Charge)
- Mounting--Front Center Stabilizer
- Control valve for operation of single stabilizer, Required w/FBS

## TRUCK

- Sterling LT7500 Single Steer Tandem Rear Chassis
- Cat C-7 300HP, 860 LB./FT. Torque, Diesel Engine
- Cruise Control
- Eaton RT 8608L Transmission, 9 Speed
- Meritor MFS-20-133A, 20K Front Axle
- Meritor RT-40-145, 40K Tandem Rear Axle
- Hendrickson RT 403, 40,000 Spring, Rear Suspension
- 4.11 Rear Axle Ratio
- Wheel Diff Locks
- Front Tires: 425/650R 22.5 Tires on Steel Disc Wheels
- Rear Tires: 11.R 22.5 Tires (Qty 8) on Steel Disc Wheels
- Dual 60 US Gallon Aluminum Fuel Tanks
- Heat/Defrost/Air Conditioning
- Air Suspension Drivers Seat
- Fixed passenger seat
- AM/FM/ Radio

**NET SELLING PRICE:..... \$ 137,000 Each USD**





[www.crane-works.com](http://www.crane-works.com)



[www.crane-works.com](http://www.crane-works.com)



